

## 2MD02, 3MD02, 4MD02, 2MD03, 3MD03, 4MD03 Electric Multi Deck Oven

### Product Features

- Electronic Controls for each deck
- Stone soles fitted to each deck
- Steam fitted to each deck
- Independent Top & Bottom heat (Temperature) control for each deck
- Full size glass viewing window
- Internal lights to each deck
- Available in 4-12 tray configurations
- Accommodates trays up to 460mm x 760mm
- Up to 21 Loaves per deck
- Modular Construction - additional decks can be added if required
- On wheels for easy movement



4MD03

## 2MD02, 3MD02, 4MD02, 2MD03, 3MD03, 4MD03 Electric Multi Deck Oven



### Technical Features

- Internal Chamber Height 240mm
- Door opening height 210mm
- Electronic control panels feature top & bottom Heat (temperature) controls, Bake timer, Digital display readouts
- Optional Setter loader available
- Fitted with castors & lock down feet
- Stainless steel external surfaces



Australia  
www.moffat.com.au  
New Zealand  
www.moffat.co.nz

Australia  
Moffat Pty Limited

Victoria/Tasmania  
740 Springvale Road  
Mulgrave, Victoria 3170  
Telephone 03-9518 3888  
Facsimile 03-9518 3833  
vsales@moffat.com.au  
www.moffat.com.au

New South Wales  
Telephone 02-8833 4111  
nswsales@moffat.com.au

South Australia  
Telephone 03-9518 3888  
vsales@moffat.com.au

Queensland  
Telephone 07-3630 8600  
qldsales@moffat.com.au

Western Australia  
Telephone 08-9202 6820  
bgarcia@moffat.com.au

New Zealand  
Moffat Limited

Christchurch  
16 Osborne Street  
Christchurch 8011  
Telephone 03-389 1007  
Facsimile 03-389 1276  
sales@moffat.co.nz

Auckland  
Telephone 09-574 3150  
sales@moffat.co.nz

Model	Width	Depth	Height	Electrical Requirements	Capacity
2MD02	1530mm	1390mm	1550mm	400-415V, 3P+N+E, 50Hz, 18kW	4 tray
3MD02	1530mm	1390mm	1875mm	400-415V, 3P+N+E, 50Hz, 27kW	6 tray
4MD02	1530mm	1390mm	1965mm	400-415V, 3P+N+E, 50Hz, 36kW	8 tray
2MD03	2020mm	1390mm	1620mm	400-415V, 3P+N+E, 50Hz, 22kW	6 tray
3MD03	2020mm	1390mm	1945mm	400-415V, 3P+N+E, 50Hz, 33kW	9 tray
4MD03	2020mm	1390mm	2200mm	400-415V, 3P+N+E, 50Hz, 44kW	12 tray

### Additional Technical Information

Additional 150mm required at rear of Oven for steam generator clearance  
Requires 1/2 inch BSP water connection to rear of oven, drainage point for excess water required

